



# EX78000 Series

## Managed Hardened 10-port 10/100BASE (8 x PoE) and 2-port Gigabit Ethernet Switch



### Value

- › Provides flexibility of 10-port 10/100BASE-TX/FX/BX/SFP plus 2-port Gigabit-TX/SX/LX/SFP
- › Port 1 to 8 supports PoE function
- › IEEE802.3at/ IEEE802.3af Power over Ethernet(PoE) support for 4 or 8 10/100BASE-TX ports
- › Wide temp range for extreme environments



15.4 W/ea or 30 W/ea



Fanless

## Features

- › Supports PoE Power Sourcing Equipment (PSE)
- › PoE control and Scheduling
- › Supports α-ring and RSTP/MSTP/STP for Ethernet redundancy
- › IP Multicast Filtering through IGMP Snooping V1, V2 & V3
- › Supports port-based VLAN and IEEE802.1Q VLAN Tagging and GVRP
- › IEEE802.1p QoS with four priority queues
- › MAC-based trunking with automatic link fail-over
- › RS-232 console, Telnet, SNMP V1, V2c & V3, RMON, Web Browser, and TFTP Management
- › Supports Command Line Interface in RS-232 Console
- › Supports IEEE802.1x Security
- › Bandwidth Rate Control
- › Per-port programmable MAC address locking
- › Up to 24 Static Secure MAC addresses per port
- › Port mirroring
- › Supports NTP
- › 1000Mbps-Full-duplex, 10/100Mbps-Full/Half-duplex, Auto-Negotiation, Auto-MDI/MDIX
- › Full wire-speed forwarding rate
- › -40°C to 75°C (-40°F to 167°F) operating temperature range, tested for functional operation @ -40°C to 85°C (-40°F to 185°F)

## Ordering Information

EX78400-00Z-P	4-port 10/100BASE-TX PoE Hardened Managed Ethernet Switch
EX78401-0YZ-P	4-port 10/100BASE-TX PoE + 1-port Gigabit Hardened Managed Ethernet Switch
EX78402-0YZ-P	4-port 10/100BASE-TX PoE + 2-port Gigabit Hardened Managed Ethernet Switch
EX78440-X0Z-P	4-port 10/100BASE-TX PoE + 4-port 100BASE-FX Hardened Managed Ethernet Switch
EX78441-XYZ-P	4-port 10/100BASE-TX PoE + 4-port 100BASE-FX + 1-port Gigabit Hardened Managed Ethernet Switch
EX78442-XYZ-P	4-port 10/100BASE-TX PoE + 4-port 100BASE-FX + 2-port Gigabit Hardened Managed Ethernet Switch
EX78800-00Z-P	8-port 10/100BASE-TX PoE Hardened Managed Ethernet Switch
EX78801-0YZ-P	8-port 10/100BASE-TX PoE + 1-port Gigabit Hardened Managed Ethernet Switch
EX78802-0YZ-P	8-port 10/100BASE-TX PoE + 2-port Gigabit Hardened Managed Ethernet Switch
EX78820-X0Z-P	8-port 10/100BASE-TX PoE + 2-port 100BASE-FX Hardened Managed Ethernet Switch
EX78821-XYZ-P	8-port 10/100BASE-TX PoE + 2-port 100BASE-FX + 1-port Gigabit Hardened Managed Ethernet Switch
EX78822-XYZ-P	8-port 10/100BASE-TX PoE + 2-port 100BASE-FX + 2-port Gigabit Hardened Managed Ethernet Switch

### 100FX Fiber Options :

- (X) = 1 : Multi Mode (SC) - 2Km  
 2 : Multi Mode (ST) - 2Km  
 6 : Multi Mode (SC) WDM-TX:1310nm/RX:1550nm - 2Km  
 7 : Multi Mode (SC) WDM-TX:1550nm/RX:1310nm - 2Km  
 8 : Multi Mode (SC) WDM-TX:1310nm/RX:1550nm - 5Km  
 9 : Multi Mode (SC) WDM-TX:1550nm/RX:1310nm - 5Km  
 A : Single Mode (SC) - 20Km  
 \*More 100FX Fiber options also available upon request.

- B : Single Mode (SC) - 40Km  
 F : Single Mode (FC) - 20Km  
 H : Single Mode (ST) - 20Km  
 P : Single Mode (SC) WDM-TX:1310nm/RX:1550nm - 20Km  
 Q : Single Mode (SC) WDM-TX:1550nm/RX:1310nm - 20Km  
 R : Single Mode (SC) WDM-TX:1310nm/RX:1550nm - 40Km  
 S : Single Mode (SC) WDM-TX:1550nm/RX:1310nm - 40Km  
 V : Support 2-port 100BASE SFP

### Gigabit Options :

- (Y) = 1 : 10/100/1000BASE-TX  
 3 : 1000BASE-SX (SC) - 550m  
 4 : 1000 BASE-SX(SC) - 2Km  
 5 : 1000 BASE-SX(ST) - 550m  
 \*More Gigabit options also available upon request.

- A : 1000BASE-LX (SC) - 10Km  
 B : 1000BASE-LX (SC) - 20Km  
 R : 1000BASE-BX (SC) WDM-TX:1310nm/RX:1550nm - 20Km  
 S : 1000BASE-BX (SC) WDM-TX:1550nm/RX:1310nm - 20Km  
 V : Support 2-port 1000BASE SFP

### Power Input Interface :

(Z) = B : DC Jack & Terminal Block

PoE Type: (P) = n/a : IEEE802.3af  
 T : IEEE802.3at

### Power Supply : (Optional)

- \*Option A - Terminal Block power supply(s), part numbers:  
 15.4W 802.3af: DD-85-48, DR-75-48, DR-120-48, SDR-240-4838  
 30W 802.3af high power: DD-85-55, DR-75-48, DR-120-48, SDR-240-48  
 \*\*Option B - DC Jack power supplies kit(s), part numbers: AS-120P-48

Installation Type : DIN Rail (mounting kit is included), Optional Panel Mount kits (KP-AA96-480) are available for ordering.

# Specifications

Technology	
Standards	<ul style="list-style-type: none"> <li>IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX/100BASE-FX, IEEE802.3ab 1000BASE-T, IEEE802.3z 1000BASE-SX/1000BASE-LX, IEEE802.3x, IEEE802.1p, IEEE802.1Q, IEEE802.1w, IEEE802.1x, IEEE802.3af</li> </ul>
Forward and Filtering Rate	<ul style="list-style-type: none"> <li>14,880pps for 10Mbps</li> <li>148,810pps for 100Mbps</li> <li>1,488,100pps for 1000Mbps</li> </ul>
Packet Buffer Memory	<ul style="list-style-type: none"> <li>2M bits</li> </ul>
Processing Type	<ul style="list-style-type: none"> <li>Store-and-Forward</li> <li>Half-duplex back-pressure and IEEE802.3x full-duplex flow control</li> </ul>
Address Table Size	<ul style="list-style-type: none"> <li>8192 MAC addresses</li> </ul>

Power	
Input	<ul style="list-style-type: none"> <li>15.4W 802.3af in 48VDC (47 - 55VDC) (Terminal Block/ DC Jack)</li> <li>30W 802.3at in 55VDC (52 - 55VDC) (Terminal Block/ DC Jack)</li> </ul>
Power Consumption	<ul style="list-style-type: none"> <li>Without PoE connections: 15W Max.</li> <li>With PoE connections: 8 ports fully-loaded 123.2W (IEEE802.3af @ 15.4W/ea) 8 ports fully-loaded 180W (Recommend 4 x IEEE802.3at @ 30W/ea + 4 x IEEE802.3af @ 15.4W/ea)</li> </ul>
Overload Current Protection	<ul style="list-style-type: none"> <li>Present</li> </ul>
Reverse Polarity Protection	<ul style="list-style-type: none"> <li>Present</li> </ul>

Mechanical	
Casing	<ul style="list-style-type: none"> <li>Metal case</li> <li>IP30</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>65mm (W) x 145mm (D) x 165mm (H) (2.56" (W) x 5.71" (D) x 6.5" (H))</li> </ul>
Weight	<ul style="list-style-type: none"> <li>1Kg (2.2lbs.)</li> </ul>
Installation	<ul style="list-style-type: none"> <li>Din-Rail (Top hat type35mm), Wall Mount</li> </ul>

Interface	
Ethernet Port	<ul style="list-style-type: none"> <li>10/100BASE-TX (PoE): 8 or 4 ports</li> <li>100BASE-FX: 0, 2 or 4 ports</li> <li>Gigabit: 0, 1 or 2 ports</li> </ul>
Console Port	<ul style="list-style-type: none"> <li>Port: One DB9 RS-232 port</li> </ul>
LED Indicators	<ul style="list-style-type: none"> <li>Per Unit: Power Status (Power 1, Power 2, Power 3)</li> <li>Per Port: PoE (Amber) for 10/100TX, 10/100TX, 100FX: Link/Activity (Green), Gigabit: Link/Activity (Green)</li> </ul>

Environment	
Operating Temperature	<ul style="list-style-type: none"> <li>-40°C to 75°C (-40°F to 167°F)</li> <li>Tested @ -40°C to 85°C (-40°F to 185°F)</li> </ul>
Storage Temperature	<ul style="list-style-type: none"> <li>-40°C to 85°C (-40°F to 185°F)</li> </ul>
Ambient Relative Humidity	<ul style="list-style-type: none"> <li>5% to 95% (non-condensing)</li> </ul>

Regulatory Approvals	
ISO	<ul style="list-style-type: none"> <li>Manufactured in an ISO9001 facility</li> </ul>
Safety	<ul style="list-style-type: none"> <li>UL508</li> </ul>
EMI	<ul style="list-style-type: none"> <li>FCC Part 15, Class A</li> <li>EN61000-6-4                             <ul style="list-style-type: none"> <li>- EN55022</li> <li>- EN61000-3-2</li> <li>- EN61000-3-3</li> </ul> </li> </ul>
EMS	<ul style="list-style-type: none"> <li>EN61000-6-2                             <ul style="list-style-type: none"> <li>- EN61000-4-2 (ESD Standards) Contact: +/- 6KV; Criteria B Air: +/- 8KV; Criteria B</li> <li>- EN61000-4-3 (Radiated RFI Standards) 10V/m, 80 to 1000MHz; 80% AM Criteria A</li> <li>- EN61000-4-4 (Burst Standards) Signal Ports: +/- 4KV; Criteria B D.C. Power Ports: +/- 4KV; Criteria B</li> <li>- EN61000-4-5 (Surge Standards) Signal Ports: +/- 1KV; Line-to-Line; Criteria B D.C. Power Ports: +/- 0.5KV; Line-to-earth; Criteria B</li> <li>- EN61000-4-6 (Induced RFI Standards) Signal Ports: 10Vrms @ 0.15 - 80MHz; 80% AM Criteria A D.C. Power Ports: 10Vrms @ 0.15 - 80MHz; 80% AM Criteria A</li> <li>- EN61000-4-8 (Magnetic Field Standards) 30A/m @ 50, 60Hz; Criteria A</li> </ul> </li> </ul>
Environmental Test Compliance	<ul style="list-style-type: none"> <li>IEC60068-2-6 Fc (Vibration Resistance) 5g @ 10 - 150Hz, Amplitude 0.35mm (Operation/Storage/Transport)</li> <li>IEC60068-2-27 Ea (Shock) 25g @ 11ms (Half-Sine Shock Pulse; Operation) 50g @ 11ms (Half-Sine Shock Pulse; Storage/Transport)</li> <li>IEC60068-2-32 Ed (Free Fall) 1M (3.281ft.)</li> </ul>

# Diagrams

Unit: mm

