



# 19" Free Standing Server Racks

Signamax 19" server racks are especially suitable for large server installations, but all other 19" components and accessories can be installed into these racks as well. The rear cover of these free standing server racks from the REC-S product range is perforated and therefore allows for higher air flow. The front door is made of safety glass and can be mounted for either left or right-hand opening. The height of the Signamax server racks ranges from 42-48U with 600 to 800 mm width. The depth of the server racks can be produced from 800 to 1,200 mm. Other dimensions are available on request.



REC-S-6421B

REC-S 19" Free Standing Server Racks RAL 7035

PART NO.	DESCRIPTION
REC-S-6421B	19" Server Rack, Height 42U, Width 600 mm, Depth 1,000 mm
REC-S-8421B	19" Server Rack, Height 42U, Width 800 mm, Depth 1,000 mm
REC-S-6451B	19" Server Rack, Height 45U, Width 600 mm, Depth 1,000 mm
REC-S-8451B	19" Server Rack, Height 45U, Width 800 mm, Depth 1,000 mm
REC-S-6481B	19" Server Rack, Height 48U, Width 600 mm, Depth 1,000 mm
REC-S-8481B	19" Server Rack, Height 48U, Width 800 mm, Depth 1,000 mm

## Fan Units

Fan units can be mounted in the lower or the upper part of the rack without affecting available rack space. Dust filters are included.

## Wheels

Four wheels (P/N REC-CB4) are available on request.

## Colour and Surface Finish

Surface is treated with pulverized colour for internal environment according to the RAL scale. Standard colour is grey (RAL 7035), black (RAL 9005) is available on request.

## Adjustable Feet

Delivery includes 4 adjustable feet. They can be adjusted up to 20 mm to compensate for uneven floors and assure high stability.

## Door Lock

There is an adjustable 3-point lock on the front door.

## Front and Side Access

The front door and the side covers can be easily opened or removed.

## Cable Entry

Cables can be installed via the slot in the lower part of the rear cover, or through the top and the bottom parts of the rack.

## Guaranteed Load Capacity

Maximum load capacity on adjustable feet is 200 kg. On a frame stand it is 400 kg. On the REC-CB4 wheels it is also 400 kg. These values are guaranteed for evenly distributed static load.

## Alternative Components Available on Request

Full door or perforated door  
Perforated side covers