

SXKJ-6-UTP-BK-SA



SOLARIX CATEGORY 6

Keystone Jacks – Tool Free

2.5/5 Gbps

250 MHz

Number of Ports	1 x RJ45
Life Cycle	1,000 plug insertions
Contact Material	50 µin gold
Termination Block	Tool free
Conductor Size and Type	AWG 26 - 22, solid
Other Material	FR according to UL94V-0
Storage Temperature	-40 to +70 °C
Operation Temperature	-10 to +60 °C
Max. Humidity Operation	93 %

The Solarix Category 6 tool free keystone are tested up to 250 MHz and therefore fully comply with the latest ANSI/TIA 568C.2, ISO/IEC 11801, and EN 50173 standards. Their termination is very quick and easy (i.e. no termination tool is required). The Solarix Category 6 tool free keystone support both T568A and T568B wiring configurations using easy to read colour-coded wiring labels. Their new contact design provide enhanced plug to jack connection integrity and enables for 1,000 plug insertions.

Part No.

Description

SXKJ-6-UTP-BK-SA

Keystone Solarix CAT6 UTP Tool Free RJ45 Black

SXKJ-6-STP-BK-SA

Keystone Solarix CAT6 STP Tool Free RJ45 Black

SXKJ-6-STP-BK-SA



SXKJ-6-UTP-BK-SA



+420 840 505 555 • info@solarix.cz
www.solarix.cz

