10G keystone Solarix CAT6A STP RJ45 quick tool





Product number: 25286903

Type number: SXKJ-10G-STP-BK-NA

EAN barcode: 8595684700282













Key features

- Quality shielded category 6A/Class Ε_Λ keystone
- Designed for ethernet protocols, including 2.5GBASE-T, 5GBASE-T, and 10GBASE-T
- Very easy installation with the guick tool pliers SXKI-NA-BU
- 50 µin gold contact plating
- Dust cover
- The keystone meets the ISO/IEC 11801, EN 50173, and ANSI/TIA 568.2-D cabling standards
- Its form factor complies with the requirements of the EN 60603-7 specifications
 (i.e. the keystone is compatible with other manufacturers' modular outlets that meet this standard)
- The colour of the keystone is black (inner parts, dust cover) and silver (metal body)
- Its electrical performance has been authorized by the FORCE TECHNOLOGY independent testing laboratory in the EC VERIFIED certification program, including the 4PPoE standard (i.e. IEEE 802.3bt)

Cabling standards

General standards EN 50173-1, EN 50173-2, ISO/IEC 11801-1, ISO/IEC 11801-2, ANSI/TIA 568.2-D

Product standards EN 60603-7-51, IEC 60512-99-002

esting authority FORCE TECHNOLOGY

Certification program EC VERIFIED, Component Level

Supported protocols

| | 10BASE-T | 100BASE-TX | 1000BASE-T | 2.5GBASE-T | 5GBASE-T | 10GBASE-T |
|--|----------|------------|------------|------------|----------|-----------|
| Supported by the SXKJ-10G-STP-BK-NA keystone | YES | YES | YES | YES | YES | YES |









Supported PoE

| | 802.3af | 802.3at | 802.3bt | 802.3bt |
|--|---------|---------|---------|---------|
| PoE type | Type 1 | Туре 2 | Туре 3 | Туре 4 |
| Maximum current | 350 mA | 600 mA | 600 mA | 960 mA |
| No. of pairs used | 2 | | | |
| Supported by the SXKJ-10G-STP-BK-NA keystone | YES | YES | YES | YES |

Physical parameters

Keystone construction STP

Number of ports 1x RJ45 8p8c

Min. port lifetime 1000 connections/disconnections

Contacts plating 50 µin gold
Termination quick tool

Size and type of conductor

AWG 26 - 22, solid wire

Material of non-metallic parts

FR plastic according to UL94-0

Keystone body colour black (inner parts, dust cover) and silver (metal body)

Operation and storage

Operating temperature -10 to 60 °C

Storage temperature -40 to 70 °C

Max. operating humidity 93%

Logistic parameters

Keystone packaging size $(h \times w \times d)$

Weight

Included in the package

Master packaging

Master packaging size ($h \times w \times d$)

Batch marking

Batch and product numbers barcode

EAN code type

 $145 \text{ mm} \times 90 \text{ mm} \times 20 \text{ mm}$, plastic bag

23 g

1x keystone, 1x plastic cap, 1x plastic strap, 1x dust cover

280x keystones

230 mm x 515 mm x 400 mm, carton box

yes (on the product, its packaging and on the transport master box)

IDAutomation Code 39, ANSI/ISO/AIM specification

EAN-13

Keystone label





10G Keystone CAT6A STP RJ45 Black Quick Termination 10G keystone CAT6A STP RJ45 černý rychlozařezávací 10G keystone CAT6A STP RJ45 czorny szybko-zaciskowy

1 pc./ks/szt.





Solarix warranties

Standard warranty 5 years
System warranty 30 years











We recognize the importance of regular checks of Solarix products that customers use in their networks. That is why we have he electrical parameters of our cables and connecting hardware tested by independent laboratories. Certificates issued by these authorities are an important part of our Solarix product support and guarantee products reliability to our customers. This is also rue for the SXKJ-10G-STP-BK-NA keystone, which has been tested by the FORCE TECHNOLOGY laboratory as part of the EC VERIFIED certification program.

Related products

| Product Number | Type Number | Description |
|----------------|-------------------------------|---|
| 26000025 | SXKD-6A-STP-LSOH | Installation Cable Solarix CAT6A STP LSOH Dca-s 1,d2,a 1 500m/reel |
| 26000037 | SXKD-6A-STP-LSOH-B2ca | Installation Cable Solarix CAT6A STP LSOH B2ca-s1,d1,a1 500m/reel |
| 26000038 | SXKD-6A-FFTP-LSOH | Installation Cable Solarix CAT6A FFTP LSOH Dca-s2,d2,a1 500m/reel |
| 26000040 | SXKD-6A-STP-PE | Installation Cable Solarix CAT6A STP PE Fca 500m/reel |
| 27000007 | SXKD-7-SSTP-LSOH | Installation Cable Solarix CAT7 SSTP LSOH Cca-s 1,d 1,a 1 1000 MHz 500m/reel |
| 27000010 | SXKD-7-SSTP-LSOHFR-B2ca | Installation Cable Solarix CAT7 SSTP LSOHFR B2ca-s1,d1,a1 1000 MHz 500m/reel |
| 27000022 | SXKD-7A-1200-SSTP-LSOHFR-B2ca | Installation Cable Solarix CAT7A SSTP LSOHFR B2ca-s1,d1,a1 1200 MHz 500m/reel |
| 24000100 | SX24M-0-STP-BK-UNI-N | Unloaded Patch Panel Solarix 24 ports Black 1U |
| 23100101 | SX9-1-0-WH | Solarix Modular Wall Outlet for 1 Keystone, White |
| 23100102 | SX9-2-0-WH | Solarix Modular Wall Outlet for 2 Keystones, White |
| 23100103 | SX9-3-0-WH | Solarix Modular Wall Outlet for 3 Keystones, White |
| 23100201 | SXF-M-1-22,5-WH-P | French Style Module Solarix 22.5 x 45mm for 1 Keystone, 90° |
| 23100202 | SXF-M-1-45-WH-P | French Style Module Solarix 45 x 45mm for 1 Keystone, 90° |
| 23100203 | SXF-M-2-45-WH-P | French Style Module Solarix 45 x 45mm for 2 Keystones, 90° |
| 23100204 | SXF-M-2-45-WH-U | French Style Module Solarix 45 x 45mm for 2 Keystones, 45° |
| 23100206 | SXF-M-1-22,5-WH-U | French Style Module Solarix 22.5 x 45mm for 1 Keystone, 45° |
| 40020082 | SXKJ-NA-BU | Terminating Tool for SXKJ-xx-yyy-BK-NA Keystones |











