



Enterprise Broadband Router

Special for large networking



Powerful management



Multiple function



BRIEF INTRODUCTION ❖❖

The TEI480T+ integrates multiple functions. It not only supports Load Balancing and backups connections automatically for each other, but supports IP address filtering, Domain Name filtering and MAC address filtering as well. Besides, port bandwidth control, port mirror, port-base VLAN for LAN ports, VPN Pass through, Dynamic DNS, Virtual Server, DMZ host, UPnP functions will help you to manage the network easily.

PRODUCT FEATURES ❖❖

- ▶ Complies with IEEE 802.3、IEEE 802.3u standards;
- ▶ Supports TCP/IP, PPPoE, DHCP, ICMP, NAT, SNTP, DNS, TFTP, ARP;
- ▶ Provides one 10/100M WAN ports and four 10/100M LAN ports;
- ▶ Specifies priority channels according to source or destination IP addresses;
- ▶ Supports MAC address binding with IP address to prevent the network access of unauthorized clients;

WHAT THIS PRODUCT DOES

Provides dual WAN to connect two ISPs and guarantee a no dropped connection network.

BENEFITS

- ❖ Supports Load Balancing and backups connections automatically for each other;
- ❖ Supports Auto MDI/MDIX;
- ❖ Supports flow statistics;
- ❖ Supports the flow control based on IP address and TCP amount;
- ❖ Supports port bandwidth control, port mirror and port-base VLAN for LAN ports;

TECHNICAL SPECIFICATIONS

Protocols and Standards	IEEE 802.3, IEEE 802.3u, TCP/IP, PPPoE, DHCP, ICMP, NAT, SNTP, DNS, TFTP
Interface	2WAN Port, 3 LAN Port
Power Supply	Internal Switch Power, AC 110-240V 50/60Hz input
Transmission Media	10Base-T: Cat. 3 or above UTP/STP, 100Base-TX: Cat. 5 UTP/STP
Operating Temperature	32 to 104°F (0 to 40°C)
Operating Humidity	10 to 90% Noncondensing
Storage Temperature	-40 to 158°F (-40 to 70°C)
Storage Humidity	5 to 90% Noncondensing
Dimension (WxDxH)	295X158X44mm (11.6"X6.2"X1.7")
Housing Material	Metal
Gross Weight	1.99Kg
Certificate	CE, RoHS

PACKAGE CONTENTS

- ❖ TEI480T+ Enterprise Broadband Router
- ❖ Power Cord
- ❖ User Manual

MINIMUM REQUIREMENTS

- ❖ Internet Explorer 5.5 or Firefox 1.0
- ❖ Network Adapter

Model No.:TEI480T

● **Obligation-free statement**

The maximum performance for wireless is derived from IEEE Standard 802.11 specifications. Actual performance can vary, including lower wireless network capacity, data throughput rate, range and coverage. Performance depends on many factors, conditions and variables, including distance from the access point, volume of network traffic, building materials and construction, operating system used, mix of wireless products used, interference and other adverse conditions. Check the product package and contents for specific features supported. Specifications are subject to change without notice.

● **Copyright statement**

Tenda is the registered trademark of Shenzhen Tenda Technology Co., LTD in CHINA and certain other countries. Copyright © 2007 Shenzhen Tenda Technology Co., LTD All rights reserved. Other brands and product name are trademarks or registered trademarks of their respective holders.

● **Contact us**

Shenzhen Tenda Technology Co., Ltd.
 Address: Tenda Industrial Park, No. 34-1, Shilong Rd., Shiyong Town, Bao'an District, Shenzhen, P.R. China 518108
 Tel: 0086.755.2765.7180 Fax: 0086.755.2765.7178
 E-mail: sales@tenda.com.cn Http: www.tenda.cn