

SXKJ-5E-UTP-BK-SA



SOLARIX CATEGORY 5E

Keystone Jacks – Tool Free

2.5/5 Gbps

100 MHz

Number of Ports	1 x RJ45
Life Cycle	1,000 plug insertions
Contact Material	50 µin gold
Termination Block	Tool free
Conductor Size and Type	AWG 26 – 22, solid
Other Material	FR according to UL94V-0
Storage Temperature	-40 to +70 °C
Operation Temperature	-10 to +60 °C
Max. Humidity Operation	93 %

The Solarix Category 5E tool free keystones are tested up to 100 MHz and therefore fully comply with the latest ANSI/TIA 568C.2, ISO/IEC 11801, and EN 50173 standards. Their termination is very quick and easy (i.e. no termination tool is required). The Solarix Category 5E tool free keystones support both T568A and T568B wiring configurations using easy to read colour-coded wiring labels. Their new contact design provide enhanced plug to jack connection integrity and enables for 1,000 plug insertions.

Part No.

Description

SXKJ-5E-UTP-BK-SA

Keystone Solarix CAT5E UTP Tool Free RJ45 Black

SXKJ-5E-STP-BK-SA

Keystone Solarix CAT5E STP Tool Free RJ45 Black

SXKJ-5E-STP-BK-SA



SXKJ-5E-UTP-BK-SA



+420 840 505 555 • info@solarix.cz
www.solarix.cz

