



Solarix ISDN Category 3 patch panels are high-density panels with 25 and 50 ports. The panels meet all electrical parameters for Category 3 and are designed for termination of two pair telecommunication cables in Krone termination blocks. Their printed circuit board design together with solid quality components ensures the Category 3 performance. Integrated back cable management for separate cables provides organized and secure installation. All ports are numbered. Solarix ISDN patch panels are available in 1U height and black colour.

## Technical parameters

Supported protocols	<b>10BASE-T and lower</b>	Colour	<b>Black</b>
Number of Ports	<b>25 and 50x RJ45</b>	Units	<b>1U</b>
Life Cycle	<b>750 plug insertions</b>	Height	<b>44 mm</b>
Contact Material	<b>15 µin gold</b>	Width	<b>484 mm</b>
IDC Block	<b>Dual 110/Krone 8p8c</b>	Depth	<b>129 mm</b>
IDC Block Life Cycle	<b>200 terminations</b>	Storage Temperature	<b>-40 to +70 °C</b>
Conductor Size and Type	<b>AWG 26 – 22, solid</b>	Operation Temperature	<b>-10 to +60 °C</b>
Other Material	<b>FR according to UL94-0</b>	Max. Humidity Operation	<b>93%</b>

Product number	Type number	Description
24024725	SX25-ISDN-BK	19" Patch Panel Solarix 25x RJ45 Black 1U
24024750	SX50-ISDN-BK	19" Patch Panel Solarix 50x RJ45 Black 1U



SX50-ISDN-BK