

SXOB-SC-SX-4



FIBRE MANAGEMENT

Fibre optic terminal wall box 4f



Protection	IP 65
Installation method	wall mounted/pole mounted
Capacity	4f
Compatibility	4x SC simplex
Number of cable entries	1x 9 mm with rubber blank
Number of cable outputs	4x 9 mm with rubber blank
Width x Depth x Height	135 x 40 x 190 mm
Weight	0,3 kg
Colour	grey RAL 7035
Operating temperature	-25 to +70 °C

Package contains

- 2x screw 4 x 20 mm
- 2x wall plug
- 1x key
- 4x splice protectors 45 mm

IP 65

The optical wall box is used to terminate fibre optic cables in outdoor and indoor installations. This optical box has a high degree of protection IP 65. The surface of the optical wall box is UV resistant. It can be mounted directly on the wall using the mounting kit. Optical box allows to terminate up to 4 fibres in combination of 4x SC simplex or 4x LC duplex, or 4x E2000. It includes 1x fibre optic cable entry with rubber cap. The output has 4 holes for patch cables fitted with a rubber cap. When the patch cable is placed, the rubber cap is cut and the patch cable is inserted inside. The optical box also includes a vertical flap cassette, ensuring easier access and handling of pigtailed. The box is lockable.

Part No.

SXOB-SC-SX-4

Description

Fibre optic terminal wall box 4f

SXOB-SC-SX-4



SXOB-SC-SX-4



+420 840 505 555 • info@solarix.cz
www.solarix.cz

